

40" TFT-LCD Monitor



FEATURES

- Displays a full, flat 40" diagonal image
- High Resolution
- High Contrast Ratio
- Wide Viewing Angle
- HD Ready
- 4 Way PIP Function
- Pivot Function

SUMMARY

SMT-3211 /4011 are 32"/40" TFT LCD monitors supports extended connectivity. PC, Video, RS-232C Loop Out function are supported.

Motion Optimizer takes visual data and automatically breaks them into signal and noise, eliminating noise and blur without the slightest damage to the original signal. For each scene, Color Optimizer calculates the saturation of red, green, and blue in the input signal and adjusts it to shades that the human eye accepts as natural. Conventional contrast enhancers produce noise boosts and flickers. DNIe™ has solved these problems by developing an epoch producing a picture rich in contrast, even in the tiniest details. Samsung security monitors have a pivot function that freely rotates around 90°, allowing you to easily view a vertical image or text.

SMT-3211 /4011 manufactured by SAMSUNG, support VESA Standard wall mount system.



40" TFT-LCD Monitor



SPECIFICATIONS

Video Standard	PAL/NTSC
LCD Panel size	40" Diagonal TFT
Scanning System	Progressive
Pixel Pitch	0.648 mm(H) x 0.648 mm(V)
Brightness	450 cd/m ²
Contrast ratio	1200:1
Response Time	8 ms
Viewing Angle	178°(H) x 178°(V)
Video Input(s)	CVBS, Component, Y/C, RGB, VGA
Resolution	1366 x 768 pixel
Screen Mode	HD Ready
PIP	On/Off
Operating Temperature	10°C ~ +40°C
Humidity	10 ~ 80%RH
Storage Temperature	-20°C ~ +45°C
Storage Humidity	5% ~ 95%, non-condensing
Supply Voltage	AC 100-240V, 50/60Hz
Power Consumption	210 W
Weight	23 kg
Dimensions w*h*d	971 x 629.5 x 223 mm

