

1/4" CMOS Network Colour Camera



---

## FEATURES

---

- 1/4" 320.000 pixels CMOS
- Preset function (Max=8)
- Remote-Control (Pan, Tilt)
- Flash LED for night vision
- PIR Sensor
- Pre Alarm / Auto Alarm
- Privacy function
- UPnP supportable
- Web Browser Viewer
- Supports WAP2.0
- Remote Recording with Free Multi-Viewer Management Software; Up to 16 CH Recording, 1 CH Playback
- IEEE 802.11b Wireless Network Adapter
- Supports WAP2.0

---

## SUMMARY

---

SNC-L200(wired) and SNC-L200W(wireless) are the network cameras which enable surveillance from remote PC under various networking environments such as ADSL, cable and modem. Its compact design fits to any interior environment. The images shot by these network cameras can be monitored and even Pan/Tilt control can be realized at remote site through a Multi-viewer designed by Samsung.

The camera automatically saves pre/post-images to users PC when it detects motion and issues an alarm. UPnP function makes it easy for users to set up IP and connect to network under various networking environments. An easy to install SNC-L200W model adopts IEEE 802.11b for operation under wireless LAN environment.



1/4" CMOS Network Colour Camera



## SPECIFICATIONS

Image Sensor	1/4" CMOS 320,000 pixels
Sensitivity	1 ~ 10,000 lux
Pan Range	± 50°
Tilt Range	40° Down ~ 10° Up
Pan Speed	50° / sec.
Number of Preset	8
Flash LED Lens Degree	45°
Flash LED Lux/Range	8lux/3m
PIR Sensor- Left/Right	40°
PIR Sensor- Up/Down	85°
PIR Sensor- Range	3m
Operating System	Embedded Linux
Browser	Internet Explorer 5.0 or Higher
Network	10/100 Base-T
Network Service	Fixed IP, Cable Modem, ADSL, DHCP, IP Router
Network Protocol	DHCP, TCP/IP, UDP/IP, ARP, HTTP, FTP, Telnet, SMTP, PPPoE
Video Compression	M-JPEG
Resolution	640x480, 320x240, 160x120
Frame Rate	15 fps at 640x480 30 fps at 320x240
Compression Rate	12KB(Low),17KB(Normal),25KB(High) at 640x480 4KB(Low),7KB(Normal),9KB(High) at 320x240 2KB(Low),3KB(Normal),4KB(High) at 160x120
IP Router(AP)- LinkSys/Netgear/D-Link	WRT54G/ WGR614v4/ DI-624+
Simultaneous Viewer	10 Persons
Pre-Alarm	Yes
Recording	Yes, save on users PC via network
DDNS	Supporting Samsung DDNS and Public DDNS servers
WAP-WAP Version	WAP2.0
WAP-Browser	Open browser
WAP-Display Size	160x320/320x240
WAP-Service area	USA
Wireless Adapter	IEEE802.11b/ 2.4GHz/ 30~40m/ 11Mbps
Operating Temperature	0°C ~ +40°C
Humidity	20 ~ 85%RH
Supply Voltage	DC 8.4V (External Adapter)
Power Consumption	5 W
Weight	0.4 kg
Dimensions w*h*d	105 x 75 x 48 mm

